

FIRE ALARM CONTROL PANEL

Brand: TYY
Model: YF1
TYPE: CONVENTIONAL
No. of Zones: 5,10

DIMENSIONS

CABINET	WALL MOUNT
No. of Zones	5,10 ZONES
H (cm)	40
W (cm)	30
D (cm)	12.6



FEATURES

- Two-Stage Fire alarm delay function.
- Standby battery protection.
- Protection against lightning surge.
- Abnormal voltage monitoring.
- Human-Centered design.
- Steel plate with coating

SPECIFICATION

ITEM	SPECIFICATION
Model	YF1
Power Source	110V AC 50/60 Hz or 220V AC 50/60 Hz
Standby Battery	24V DC
Charging Voltage	Below 26.4V DC 450mA, trickle Charging
Circuit Voltage	24V DC operation voltage,
Tated Impedance	Under 50Ω, Ground Resistance aboce 2MΩ
Detector Connection	No limitation for Conventional Rate of Rise Heat or Fixed Temperature Heat Detector; Up to 30 Photoelectric Smoke Detector (per zone)
E.O.L. Resistor	10KΩ
No. of Indicators	1.2 times of the number of zone (LED indicating lamp)
No. of Bells	1.2 times of the number of zone
Cabinaet Material	Steel plate with coating
Main Audio	Mono tone sounder (above 85dB for 1m distance)

